

IEI Technology Corp.
2010 Catalog Correction (Panel PC Catalog)

Correction period: 2010.10.1~2010.10.31

Category	Page	DM-65GHS/R-	Location	Original Data	Correction
1. Automation Panel Solutions	1-127	WIDS-515A/517A	Dimensions		WIDS-517A/9455's dimensions changed with WIDS-515A/9455's dimensions.
	1-128	PPC-2706GHS/LX-800 PPC-	Model name	PPC-2706GHS/LX-800 PPC-2708GHS/LX-800	PPC-2706GS-LX PPC-2708GS-LX
			Features	1. 6.5" TFT VGA LCD / 8.4" TFT SVGA LCD	1. Industrial Panel PC with touch screen
			Specifications	PPC-2706GHS/LX-800 PPC-2708GHS/LX-800	PPC-2706GS-LX PPC-2708GS-LX
			Fully Integrated I/O	PPC-2708GHS	PPC-2708GS
	1-129	PPC-2706GHS/LX-800 PPC-	Dimensions (Unit: mm)	PPC-2708GHS	PPC-2708GS
			Options	PPC-2706GS/LX PPC-2708GHS/LX	PPC-2706GS-LX PPC-2708GS-LX
			Options: LCD Monitor Stand Din Mounting Kits	LCD Monitor Stand Din Mounting Kits PPC-2706GS-LX: STAND-100-RS/DK-084MS PPC-2708GS-LX: STAND-100-RS/DK-084MS	LCD Monitor Stand Din Mounting Kits PPC-2706GS-LX: STAND-100-RS PPC-2708GS-LX: STAND-100-RS
			Options: Din Mounting Kits		Deleted
			Packing List	Jumper Pack: 33101-000249-RS x1 Power Cord: 32000-000002-RS x1 Power Adapter: 63000-FSP050DBAB1411-RS - 50W x1 PS/2 Cable: 32000-133200-RS x1 Din Mounting Kit: 19Z00-000025-R10 (PPC-2706GS/LX) x1 HDD IDE Cable: 32200-074700-RS x2	Jumper Pack: 33100-000033-RS x5 Power Cord: 32000-000002-RS (European Standard) x1 Power Adapter: 63000-FSP060DBAB1552-RS x1 PS/2 Cable: 32000-134400-RS x1 Din Mounting Kit: DK-084MS (For PPC-2706G only) x1 HDD IDE Cable: 32200-074700-RS 200MM, IDE 44P x2
					Add: One Key Recovery CD : IEI-7B000-000478-RSx1
	1-155	Workstation	Packing Information	32000-078400-RS	This is option cable. Deleted.
	1-175	Heavy Industrial Display Monitors	Support analog VGA or DVI	DM series	Display Monitor series
			Full OSD Function in the front panel	DM series	Display Monitor series
			Hi-optical RS-232 interface touch screen	Hi-optical RS-232 interface touch screen	Hi-optical RS-232 & USB interface touch screen
				DM series IEI DM provides T-R model with high strength Fiber Glass Touch Screen for appliances.	Display Monitor series IEI Display Monitor series provides R model with high strength Fiber Glass Touch Screen for appliances.
	1-176	DM Series	Description	7"-12.1" R20 Version Comes with LED Backlight TFT LCD and -20°C~60°C extended temperature	6.5"-12.1" R20 Version Comes with LED Backlight TFT LCD and -10°C~50°C extended temperature
			Features	2. Optional RS-232 interface touch	2. Optional RS-232 & USB interface touch screen
		DM-65GHS	Operating Temperature	-10°C~60°C	-10°C~50°C
		DM-84GHS	Operating Temperature	-10°C~60°C	-10°C~50°C
		DM-104GHS	Operating Temperature	-10°C~60°C	-10°C~50°C
		DM-121GXS	Operating Temperature	-10°C~60°C	-10°C~50°C
		DM-150GS	Operating Temperature	-10°C~60°C	0~50°C
		DM-170GS	Operating Temperature	-10°C~60°C	0~50°C
		DM-190GS	Operating Temperature	-10°C~60°C	0~50°C
		DM-150GS	Power Adapter	45W, 63000-FSP060DBAB1552-RS	50W, 63000-FSP050DBAB1411-RS
		DM-170GS	Power Adapter	45W, 63000-FSP060DBAB1552-RS	50W, 63000-FSP050DBAB1411-RS
	DM-190GS	Power Adapter	45W, 63000-FSP060DBAB1552-RS	50W, 63000-FSP050DBAB1411-RS	

IEI Technology Corp.
2010 Catalog Correction (Panel PC Catalog)

1-177	DM Series	Packing List		<p>Changed as below: 1 x AC power cable: 32702-000200-100-RS /1750mm, European Standard 1 x VGA cable: 32000-036200-RS / 1800mm 1 x 50W AC power adapter : 63000-FSP050DBAB1411-RS / For DM-150GS / 170GS / 190GS series 1 x 36W AC power adapter : 63000-FSP036RAB610-RS / For DM-65GHS / 84GHS / 104GHS / 121GS series 1 x User manual & Driver CD: 7B000-000087-RS 1 x Power cable for terminal block: 32100-041001-RS / For M Model 1 x Touch screen Kit (RS-232 & USB Cable / Touch Pen) : 32000-000098-RS & 32000-045801-RS / For R model</p>
	DM-65GHS/R-R20	Ordering Information	6.5" 700cd/m ² High luminance VGA LCD monitor with VGA, Aluminum front panel, Silver color, W/8.4" Touch screen.	6.5" 800cd/m ² High luminance VGA LCD monitor with VGA, Aluminum front panel, Silver color, W/ Touch screen, R20, RoHS
	DM-121GXS/R-R20	Ordering Information	2.1" 500cd/m ² XGA LCD monitor, Aluminum front panel, Silver color.W/Touch screen, R20, RoHS	12.1" 500cd/m ² XGA LCD monitor, Aluminum front panel, Silver color,W/Touch screen, R20, RoHS
1-183	LCD Kits Series	Ordering Information	LCD-KIT170GS-R20	LCD-KIT170G-R20