

IEI Technology Corp.
2011 Catalog Correction (IPC Catalog)

Correction period: 2011.10.1~2011.10.31

Category	Page	Model Name	Location	Original Data	Correction
1. Single Board Computer	1-4	SPCIE-5100DX	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-6	SPCIE-5100P	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-9	PCIE-Q57A	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-10	PCIE-G41A2	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-11	PCIE-Q350-R11 PCIE-9652	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-16	PXE-13S-R42	Model Name	PXE-13S-R42	PXE-13S-R50
	1-19	WSB-G41A	CPU compare table	945G: ICH Support: ICH7R	945G: ICH Support: ICH7
	1-19	WSB-G41A	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-20	PX-10S-RS-R41	Model Name	PX-10S-RS-R41	PX-10S-RS-R50
	1-20	WSB-PV-D4251/D5251	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-21	WSB-Q354-R40 WSB-9454-R40	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-22	WSB-9452-R40 WSB-945GSE	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-23	ROCKY-4786EVG-RS-R41 ROCKY-3786EVGU2-RS-	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-29	PX-14S3-RS-R41 PX-14S5-RS-R41	Model Name	PX-14S3-RS-R41 PX-14S5-RS-R41	PX-14S3-RS-R50 PX-14S5-RS-R50
	1-36	PIC0e-PV-D4251/N4551/D5251	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-37	PIC0e-PV-D510 PIC0e-945GSE	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-38	PIC0e-GM45A PIC0e-9452-R21	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-43	PCISA-PV-D4251/N4551/D5251	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-44	PCISA-945GSE-R11	Ordering Information	19800-00110-RS	Changed: 19800-004300-100-RS
		PCISA-9652		19800-00110-RS	Changed: 19800-004300-100-RS
	1-44	PCISA-945GSE-R11	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-45	PCISA-9652 / PCISA-6770E2-RS-R30	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-52	IOWA-LX	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-53	IOWA-8522/IOWA-MARK-R11	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-87	KINO-G45A	Packing List	CB-USB02-RS	19800-003100-200-RS
	1-121	WAFER-945GSE2	modle name	WAFER-945GSE2	WAFER-945GSE2-R20
			Specification	Ethernet : Dual Realtek RTL8111CP PCIe GbE controllers	Ethernet : Dual Realtek RTL8111E PCIe GbE controllers
				Audio: Realtek ALC655 with AC'97 codec	Audio: Realtek ALC662 with HD codec
				Temperature Operation: 0°C ~ 60°C (WAFER-945GSE2-N270-R10) Operation: -20°C ~ 70°C (WAFER-945GSE2-N270W-R10)	Temperature Operation: 0°C ~ 60°C (WAFER-945GSE2-N270-R20) Operation: -20°C ~ 70°C (WAFER-945GSE2-N270W-R20)
				Power Consumption : 5V@3.1A (Intel® Atom™ N270 1.6G with on-board 1GB DDR2)	Power Consumption : 5V@2.36A (Intel® Atom™ N270 1.6G with on-board 1GB DDR2)
			Dimensions		Changed

			Ordering Information	<p>WAFER-945GSE2-N270-R10: 3.5" SBC with Intel® Atom™ processor N270 1.6G, VGA/LVDS, Dual GbE,CFII, USB, SATA, on board 1GB memory and PC/104</p> <p>WAFER-945GSE2-N270W-R10: 3.5" SBC with Intel® Atom™ processor N270 1.6G, VGA/LVDS, Dual GbE,CFII, USB, SATA, on board 1GB memory and PC/104, -20~70°C</p>	<p>WAFER-945GSE2-N270-R20: 3.5" SBC with Intel® Atom™ processor N270 1.6G, VGA/LVDS, Dual GbE,CFII, USB, SATA, on board 1GB memory and PC/104</p> <p>WAFER-945GSE2-N270W-R20: 3.5" SBC with Intel® Atom™ processor N270 1.6G, VGA/LVDS, Dual GbE,CFII, USB, SATA, on board 1GB memory and PC/104, -20~70°C</p>
	1-128	IEM-945GSE	Ordering Information	34000-000180-RS	Deleted
	1-139	PM-PV-N4551/D5251	Description	PC/104 SBC with Intel® Atom™ N455/D525, DDR3, VGA/LVDS, GbE, USB 2.0, SATA 3Gb/s and CF Type II, RoHS	PCI-104 SBC with Intel® Atom™ N455/D525, DDR3, VGA/LVDS, GbE, USB 2.0, SATA 3Gb/s and CF Type II, RoHS
3. Embedded Computing Solutions	3-12	Uibx-200	Specifications		<p>Add:</p> <p>uIBX-200-VX800A (uIBX-200-VX800B)</p> <p>Storage: CompactFlash®: 1 SD Card: N/A</p> <p>uIBX-200-Z510</p> <p>Storage: CompactFlash®: 1 2 x SD Card Slot (Internal)</p>
7. Power Supply/Peripheral	7-52	CF-1156A-RS	Model Name	CF-1156A-RS	CF-1156A-RS-R11
			Specifications	Dimensions: 84 x 84 x 28(mm)	Dimensions: 89 x 89.6 x 27.4(mm)
	7-64	19800-00110-RS	Cable and Connectors	19800-00110-RS	Changed: 19800-004300-100-RS
	7-65	CB-USB02-RS	Model Name	CB-USB02-RS	19800-003100-200-RS
	7-11	ACE-A225A	IU AC Input	-5V: 0.5A -12V: 3.0A +5 Vsb: 0.3A	-5V: 0.3A -12V: 0.5A +5 Vsb: 3A

