

IEI Technology Corp.
2011 Catalog Correction (Panel Catalog)

Correction period: 2012.1.1~2012.1.31

Category	Page	Model Name	Location	Original Data	Correction
	2-3	E. Wireless Capabilities	Compare Table	Optional HSUPA	Deleted
	2-6	5.7"~8.4" Selection Guide	Optional HSUPA Modem		Deleted
	2-7	Wide 10.2"~12.1" Selection Guide	Optional HSUPA Modem	Optional (internal USB)	Deleted
	2-8	15" Selection Guide	Optional HSUPA Modem	Optional (internal USB)	Deleted
		AFL-15A(E)-N270 AFL-15D(E)-N270	HDD	1 x 2.5" IDE HDD bay or Optional HSUPA Module	1 x 2.5" IDE HDD bay
	2-9	AFL-W15A-N270 AFL-W15B-N270 AFL-W15A-GM45	Optional HSUPA Modem	Optional (internal USB)	Deleted
			HDD	1 x 2.5" SATA HDD bay or Optional HSUPA module	1 x 2.5" SATA HDD bay
	2-10	17" Selection Guide	Optional HSUPA Modem	Optional (internal USB)	Deleted
		AFL-17A-915	HDD	1 x 2.5" SATA HDD bay or Optional HSUPA Module	1 x 2.5" SATA HDD bay
	2-11	19"~Wide 19" Selection Guide	Optional HSUPA Modem	Optional (internal USB)	Deleted
	2-17	AFL2-12A-D525	Expansion Interface	2 x PCIe by one expansion interface for LAN card expansion 1 x PCIe Mini slot for WiFi 1 x PCIe Mini slot reserved	1 x PCIe by one expansion interface for LAN card expansion 1 x PCIe Mini slot for WiFi 1 x PCIe Mini slot reserved
			Safety&EMC	CE / FCC / CB / CCC	CE / FCC
			Wireless	1 x Optional HSUPA mobile module (PCIe mini card interface) (Support GSM 850, EGSM 900, DCS 1800 & 1900) 1 x Wireless LAN 802.11 b/g/n module (internal PCIe mini card interface) 1 x Bluetooth function (internal USB interface, bluetooth V2.1+EDR) Supported Bands *HSPA/UMTS — 800/850/900/1900/2100 MHz *Quad-band EDGE/GPRS/GSM — 850/900/1800/1900 MHz *Dual-band EV-DO/CDMA — 800/1900 MHz	1 x Wireless LAN 802.11 b/g/n module (internal PCIe mini card interface) 1 x Bluetooth function
	2-19	AFL2-W15A	Ordering Information	AFL2-W15A-N270/R/1G-R10: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, bluetooth module, resistive touch screen, 1.3 M camera, microphone, 1GB DDR2 RAM, RoHS	AFL2-W15A-N270/R/1G-R11: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, resistive touch screen, 1.3 M camera, microphone, 1GB DDR2 RAM, RoHS
				AFL2-W15A-N270/R-EM/1G-R10: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, bluetooth module, resistive touch screen, 1.3M camera, microphone, 1GB DDR2 RAM, EM card reader	AFL2-W15A-N270/R-EM/1G-R11: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, resistive touch screen, 1.3M camera, microphone, 1GB DDR2 RAM, EM card reader

			AFL2-W15A-N270/R-MF/1G-R10: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, bluetooth module, resistive touch screen, 1.3 M camera, microphone, 1 GB DDR2 RAM, Mifare card reader	AFL2-W15A-N270/R-MF/1G-R11: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, resistive touch screen, 1.3 M camera, microphone, 1 GB DDR2 RAM, Mifare card reader
			AFL2-W15A-L325/R/1G-R10: 15.6" 250cd/m ² WXGA+ panel PC with AMD 780E + L325 dual core 1.5 GHz CPU, 802.11b/g/n wireless module, bluetooth module, resistive touch screen, 1.3 M camera, microphone, 1GB DDR2 RAM, RoHS	AFL2-W15A-L325/R/1G-R11: 15.6" 250cd/m ² WXGA+ panel PC with AMD 780E + L325 dual core 1.5 GHz CPU, 802.11b/g/n wireless module, resistive touch screen, 1.3 M camera, microphone, 1GB DDR2 RAM, RoHS
			AFL2-W15A-L325/R-EM/1G-R10: 15.6" 250cd/m ² WXGA+ panel PC with AMD 780E + L325 dual core 1.5GHz CPU, 802.11b/g/n wireless module, bluetooth module, resistive touch screen, 1.3M camera, microphone, 1GB DDR2 RAM, EM card reader	AFL2-W15A-L325/R-EM/1G-R11: 15.6" 250cd/m ² WXGA+ panel PC with AMD 780E + L325 dual core 1.5GHz CPU, 802.11b/g/n wireless module, resistive touch screen, 1.3M camera, microphone, 1GB DDR2 RAM, EM card reader
			AFL2-W15A-L325/R-MF/1G-R10: 15.6" 250cd/m ² WXGA+ panel PC with AMD 780E + L325 dual core 1.5 GHz CPU, 802.11b/g/n wireless module, bluetooth module, resistive touch screen, 1.3 M camera, microphone, 1GB DDR2 RAM, Mifare card reader	AFL2-W15A-L325/R-MF/1G-R11: 15.6" 250cd/m ² WXGA+ panel PC with AMD 780E + L325 dual core 1.5 GHz CPU, 802.11b/g/n wireless module, resistive touch screen, 1.3 M camera, microphone, 1GB DDR2 RAM, Mifare card reader
2-22	AFL-15i(E)-HM55 AFL-17i-HM55 AFL-19i(E)-HM55	Specifications: Optional HSUPA module(Optional)	1 x HSUPA mobile module (USB interface)	Deleted
2-27	AFL-07A-LX AFL-07A-N270	Features	* Built-in Bluetooth module	Deleted
		Icon	Bluetooth icon	Deleted
		Specifications	Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	Deleted
2-29	AFL-08AH-LX AFL-08AH-N270	Features	* Built-in Bluetooth module	Deleted
		Icon	Bluetooth icon	Deleted
		Specifications	Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	Deleted
2-32	AFL-F08A	Features	* Integrated Bluetooth 2.0 module	Deleted
		Icon	Bluetooth icon	Deleted
2-38	AFL-08B-N270	Features	* Built-in Bluetooth module	Deleted
		Icon	Bluetooth icon	Deleted

		Specifications: Wireless Connection	1 x Wireless Lan 802.11 b/g/n Module (internal PCIe mini card interface) 1 x Bluetooth module (internal USB interface, Bluetooth V2.0)	1 x Wireless Lan 802.11 b/g/n Module (internal PCIe mini card interface)
2-40	AFL-W10A-N270	Features	* Built-in Bluetooth module	Deleted
		Icon	Bluetooth icon	Deleted
		Specifications: Wireless Connection	1 x Wireless Lan 802.11 b/g/n Module (internal PCIe mini card interface) 1 x Bluetooth Function (internal USB interface, Bluetooth V2.0)	1 x Wireless Lan 802.11 b/g/n Module (internal PCIe mini card interface)
2-42	AFL-10A-N270	Features	* Built-in HSUPA module for mobile connection (Optional)	Deleted
		Icon	3.75G HSUPA and Bluetooth icon	Deleted
		Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 &	1 x Optional HSUPA Mobile Module (internal USB Interface)	Deleted
2-43		Ordering Information	AFL-10A-LX24V/R/256-R22	AFL-10A-LX24V/R/512-R22
			Note: Please order HSUPA02 for HSUPA function Note: AFL-10A-LX24V model is without power adapter	Note: Please order HSUPA02 for HSUPA function
2-44	AFL-12A-LX AFL-12A-N270	Features	* Built-in HSUPA module for mobile connection (Optional)	Deleted
		Icon	3.75G HSUPA and Bluetooth icon	Deleted
		Specifications: Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	1 x HSUPA Mobile Module (USB Interface)	Deleted
2-46	AFL-12A-LX AFL-12A-N270	Ordering Information	AFL-12A-LX/R/256-R21 AFL-12A-LX/R/512-R21 AFL-12A-LX24V/R/256-R21 AFL-12A-LX24V/R/256-R21 AFL-12A-N270/R/1G-R21	AFL-12A-LX/R/256-R22 AFL-12A-LX/R/512-R22 AFL-12A-LX24V/R/256-R22 AFL-12A-LX24V/R/256-R22 AFL-12A-N270/R/1G-R22
			Note 1 : Capacitive type touch screen is upgradable. Note 2 : Please order HSUPA02 for HSUPA function. Note 3: AFL-12A-LX24V model is without power adapter	Note 1 : Capacitive type touch screen is upgradable. Note 3: AFL-12A-LX24V model is without power adapter
2-47	AFL-15A(E)-N270	Features	* Built-in Bluetooth module * Optional HSUPA module for mobile connection	Deleted
		Icon	3.75G HSUPA and Bluetooth icon	Deleted

IEI Technology Corp.
2011 Catalog Correction (Panel Catalog)

		Specifications: Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	1 x 2.5" SATA HDD bay or Optional HSUPA module (USB interface)	Deleted
2-48	AFL-15i(E)-HM55	Icon	3.75G HSUPA and Bluetooth icon	Deleted
		Specifications: Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	1 x HSUPA Mobile Module (USB interface) (Optional)	Deleted
2-49	AFL-15i(E)-HM55	Ordering Information	Note 1: AFL-15D(E)-N270 make to project base order Note 2: Please order HSUPA02 for HSUPA function.	Note 1: AFL-15D(E)-N270 make to project base order
2-51	AFL-W15A-N270 AFL-W15A-GM45	Icon	Bluetooth icon	Deleted
		Features	* Built-in bluetooth technology * Built-in HSUPA module for mobile connection (Optional)	Deleted
2-52	AFL-W15A-N270 AFL-W15B-N270 AFL-W15A-GM45	Specifications: Wireless Connection	1 x Wireless Lan 802.11 b/g/n Module (internal PCIe mini card interface) 1 x Bluetooth Function (internal USB interface,Bluetooth V2.0)	1 x Wireless Lan 802.11 b/g/n Module (internal PCIe mini card interface)
		Specifications: Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	1 x 2.5" SATA HDD bay or 1 x HSUPA Mobile Module (USB Interface) (Optional)	1 x 2.5" SATA HDD bay
2-53	AFL-W15A-N270 AFL-W15B-N270 AFL-W15A-GM45	Ordering Information	Note 1: AFL-W15B-N270 make to project base order Note 2: Please order HSUPA02 for HSUPA function.	Note 1: AFL-W15B-N270 make to project base order
2-54	AFL-17i(E)-HM55 AFL-517A-GM45	NEW HM55 Platform Features	Icon	3.75G HSUPA and Bluetooth icon
		Specifications: Optional HSUPA Module	1 x HSUPA Mobile Module (USB Interface) (Optional)	Deleted
2-55	AFL-17D-N270 AFL-17D-GM45	Specifications: Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	1 x HSUPA Mobile Module (USB Interface) (Optional)	Deleted
2-57	AFL-17D-N270 AFL-17D-GM45	Ordering Information	Note 1: Please order HSUPA02 for HSUPA function.	Deleted
2-58	AFL-19i(E)-HM55	Icon	3.75G HSUPA icon	Deleted

		Specifications: Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	1 x HSUPA Mobile Module (USB Interface) (Optional)	Deleted
2-59	AFL-19i(E)-HM55	Ordering Information	Note : Please order HSUPA02 for HSUPA function.	Deleted
2-60	AFL-W19A/B-N270 AFL-W19A/B-GM45	Icon	3.75G HSUPA and Bluetooth icon	Deleted
		Features	Built-in HSUPA module for mobile connection (optional)	Deleted
2-61	AFL-W19A/B-N270 AFL-W19A/B-GM45	Specifications: Optional HSUPA Module (support GSM 850, EGSM 900, DCS 1800 & 1900)	1 x HSUPA mobile module (USB Interface) (Optional)	Deleted
2-62	AFL-W19A/B-N270 AFL-W19A/B-GM45	Ordering Information	AFL-W19A-N270/R/1G-R22 19" 300cd/m ² 1440x900 panel PC with Intel® Atom™ N270 1.6GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n wireless module, touch screen, 300K camera, microphone, R22	AFL-W19A-N270/R/1G-R21 19" 300cd/m ² 1440x900 panel PC with Intel® Atom™ N270 1.6GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n wireless module, touch screen, 300K camera, microphone, R21
			AFL-W19A-GM45-CM5/R/1G-R21 19" 300cd/m ² 1440x900 panel PC with Celeron® M 2.0GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, R21, RoHS	AFL-W19A-GM45-CM5/R/1G-R22 19" 300cd/m ² 1440x900 panel PC with Celeron® M 2.0GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, R22
			AFL-W19A-GM45-P84/R/2G-R21 19" 300cd/m ² 1440x900 panel PC with Core™2 Duo P:8400 2.26GHz CPU, 2GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, R21, RoHS	AFL-W19A-GM45-P84/R/2G-R22 19" 300cd/m ² 1440x900 panel PC with Core™2 Duo P:8400 2.26GHz CPU, 2GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, R22
			AFL-W19A-GM45-T94/R/2G-R21 19" 300cd/m ² 1440x900 panel PC with Core™2 Duo T9400 2.53GHz CPU, 2GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, R21, RoHS	AFL-W19A-GM45-T94/R/2G-R22 19" 300cd/m ² 1440x900 panel PC with Core™2 Duo T9400 2.53GHz CPU, 2GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, R22
			AFL-W19B-N270/RD/1G-R21 19" 300cd/m ² 1440x900 panel PC with Intel® Atom™ N270 1.6GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, DVD-RW, R21	AFL-W19B-N270/RD/1G-R22 19" 300cd/m ² 1440x900 panel PC with Intel® Atom™ N270 1.6GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, DVD-RW, R22

			AFL-W19B-GM45-CM5/RD/1G-R21 19" 300cd/m ² 1440x900 panel PC with Celeron® M 2.0GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, DVD-RW, R21, RoHS	AFL-W19B-GM45-CM5/RD/1G-R22 19" 300cd/m ² 1440x900 panel PC with Celeron® M 2.0GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, DVD-RW, R22
			AFL-W19B-GM45-P84/RD/2G-R21 19" 300cd/m ² 1440x900 panel PC with Core™2 Duo P8400 2.26GHz CPU, 2GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, DVD-RW, R21, RoHS	AFL-W19B-GM45-P84/RD/2G-R22 19" 300cd/m ² 1440x900 panel PC with Core™2 Duo P8400 2.26GHz CPU, 2GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, DVD-RW, R22
			AFL-W19B-GM45-T94/RD/2G-R21 19" 300cd/m ² 1440x900 panel PC with Core™2 Duo T9400 2.53GHz CPU, 2GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, DVD-RW, R21, RoHS	AFL-W19B-GM45-T94/RD/2G-R22 19" 300cd/m ² 1440x900 panel PC with Core™2 Duo T9400 2.53GHz CPU, 2GB DDR2 RAM, 802.11 b/g/n WiFi, touch screen, 300K camera, microphone, DVD-RW, R22
			Note: Please order HSUPA02 for HSUPA function.	Deleted
2-130	PPC Series Naming Rules			Deleted
2-132	6.5"~10.4" PPC Selection Guide			All LED icon deleted.
	PPC-2708GS-LX800	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-3708GS-945	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-3708A-N270	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-3710GS-945	Backlight MTBF (hrs)	50000	50000 (LED backlight)
2-133	10.4"~12.1" PPC Selection Guide			All LED icon deleted.
	PPC-3710A-N270	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-2710GS-LX800	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-3712GXS-945	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-3712A-N270	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-3712B-N270	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-2712GS-LX800	Backlight MTBF (hrs)	50000	50000 (LED backlight)
2-134	15" PPC Selection Guide			LED icon deleted.
	PPC-5150A/9455	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-5150A-G41	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	WIDS-515A/9455	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	WIDS-515A-G41	Backlight MTBF (hrs)	50000	50000 (LED backlight)
2-135	PPC-5170A/9455	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-5170A-G41	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	WIDS-517A/9455	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	WIDS-517A-G41	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-5190A/9455	Backlight MTBF (hrs)	50000	50000 (LED backlight)
	PPC-5190A-G41	Backlight MTBF (hrs)	50000	50000 (LED backlight)

	2-143	IEI's New PPC-3712BA/BT Supports More Features as	IEI's New PPC-3712BA/BT Supports More Features as		PPC-3712BA/BT Supports More Features as :
				85~264 V AC or 36~72 V DC power supply built-in without external power adapter	85~264 V AC power supply built-in without external power adapter
				A: PPC-3712BA-N270/890/R/1G-R20	PPC-3712BA- N270/890/R/1G-R20
	2-144	PPC-3712	Ordering Information	PPC-3712BT- N270/709/R/1G-R30	Deleted
	2-156	UPC-12A(H)/910	Ordering Information		Deleted
	2-162	SAILORPC-12A	Ordering Information	SAILORPC-12A/R/1/1-C6-R20 SAILORPC-12A/R/1/4-X-R20 SAILORPC-12A/R/1/16-X-R20 SAILORPC-12A/R/1/4-L-R20 SAILORPC-12A/R/1/16-L-R20 SAILORPC-12ASR/R/1/1-C6-R20 SAILORPC-12ASR/R/1/4-X-R20 SAILORPC-12ASR/R/1/16-X-R20 SAILORPC-12ASR/R/1/4-L-R20 SAILORPC-12ASR/R/1/16-L-R20	SAILORPC-12A/R/1/1-C6-R21 SAILORPC-12A/R/1/4-X-R21 SAILORPC-12A/R/1/16-X-R21 SAILORPC-12A/R/1/4-L-R21 SAILORPC-12A/R/1/16-L-R21 SAILORPC-12ASR/R/1/1-C6-R21 SAILORPC-12ASR/R/1/4-X-R21 SAILORPC-12ASR/R/1/16-X-R21 SAILORPC-12ASR/R/1/4-L-R21 SAILORPC-12ASR/R/1/16-L-R21
	2-163	UPC-12A	Features	An onboard ULV Intel® Celeron® M 1GHz plus 512K with Intel® 910GMLE chipset support	Deleted
	2-164	UPC-12A	Smart Battery Backup: Smart Battery Runtime	Intel®910GMLE 40~60 mins	Deleted
	2-165	UPC-12A	Intel® 910GMLE		Deleted
	2-168	UPC-12A	Specifications	UPC-12A/910 UPC-12AH/910	Deleted
2-169	UPC-12A	Ordering Information	UPC-12A/910-CM373/WT-R/1GB-R10 UPC-12AH/910-CM373/WT-R/1GB-R10	Deleted	
RISC-based Solution	4-2	RISC-based Solutions : The best platform for embedded system and Panel PC	Feature	7": 1. PoE available 2. MPEG 1/2/4 support 3. Built-in WiFi 802.11b/g function	7": 1. PoE available 2. MPEG 1/2/4 support
	4-4	IOVU-430M	Specification	Operating Temperature (°C): -20°C~50°C	Operating Temperature (°C): 0°C~50°C
	4-7	IOVU-430M	Specification	Operating Temperature (°C): -20°C~50°C	Operating Temperature (°C): 0°C~50°C
			Specification	Storage Temperature (°C): -20°C ~ 80°C	Storage Temperature (°C): -20°C ~ 60°C