

IEI Technology Corp.
2011 Catalog Correction (IPC Catalog)

Correction period: 2012.2.1~2012.2.29

Category	Page	Model Name	Location	Original Data	Correction
1. Industrial Computing	1-70	IMB-Q670-R20	Picture	8 x RS-422/485	8 x RS-232
	1-137	IQ7-DB-MITX	Specifications	Display Interface: VGA DB15 connector (SDVO to VGA by Chrontel CH7021A)	Display Interface: VGA DB15 connector (SDVO to VGA by Chrontel CH7317B)
3. Embedded Computing	3-1	EBC-2100	5. Embedded Chassis Series	EBC-2100: NANO-8522, NANO-LX	EBC-2100: NANO-LX
	3-5	TANK-GM45A	Ordering Information	63000-FSP060DBAB1554-RS: Power adapter; FSP060-DBAB1554; VAC:90V~264V; 12V/60W with ERP and PSE certifi cates	63000-FSP060DBAB1554-RS: Power adapter; FSP060-DBAB1554; Input VAC: 90~264V ; Output:12V/60W with ERP and PSE certifi cates
				63000-FSP096AHB-RS: Power adapter; FSP096-AHB; VAC:90V~264V; 12V/96W with ERP and PSE certifi cates	63000-FSP096AHB-RS: Power adapter; FSP096-AHB; Input VAC: 90~264V ; Output:12V/96W with ERP and PSE certifi cates
	3-7	TANK-101B	Specifications	Platform	Deleted
	3-9	Wstrider-200	Specifications	Platform	Deleted
	3-25	EBC-2100	Motherboard Model	NANO-8522, NANO-LX	NANO-LX
	3-26	EBC-2100	Specifications	NANO-8522, NANO-LX	NANO-LX
5. Panel Solution Introduction	5-4	IOVU-751R	Specifications	LCD Brightness (cd/m ²): 400	LCD Brightness (cd/m ²): 500
7. Power Supply / Peripherals	7-2	ACE-710APM	Medical table		EOL
			-40°C ~ 70°C table		EOL
	7-3	ACE-710APM			EOL
	7-5	ACE-710APM			EOL
	7-33	FSP120AAB	Operating Temperature	0°C ~ 50°C	0°C ~ 40°C
	7-53	CF-519-RS			EOL