

Correction period: 2012.3.1~2012.3.31

Category	Page	Model Name	Location	Original Data	Correction
2. Automation Panel Solutions	2-26	AFL-057A-Z510/Z530	PoE introduction page (Upper section)	Indication line of Power & Data	Exchange indication of Power and Data
	2-134	WIDS-515A-G41	Product Information		Delete (Product Fail)
	2-135	WIDS-517A-G41	Product Information		Delete (Product Fail)
	2-146	WIDS-515A-G41	Product Information		Delete (Product Fail)
	2-148	WIDS-515A-G41	Ordering Information	WIDS-515A-G41-E15/R/1G-R10 WIDS-515A-G41-Q94/R/1G-R10 WIDS-515AD-G41-E15/R/1G-R10 WIDS-515AD-G41-Q94/R/1G-R10	Delete (Product Fail)
	2-150	WIDS-517A-G41	Product Information		Delete (Product Fail)
	2-150	WIDS-517A-G41	Ordering Information	WIDS-517A-G41-E15/R/1G-R10 WIDS-517A-G41-Q94/R/1G-R10 WIDS-517AD-G41-E15/R/1G-R10 WIDS-517AD-G41-Q94/R/1G-R10	Delete (Product Fail)
	2-171	WIDS-517A-G41 WIDS-515A-G41	Product Information		Delete (Product Fail)
	2-171	WIDS-517A-G41 WIDS-515A-G41	Ordering Information	WIDS-515A-G41-E15/R/1G-R10 WIDS-515A-G41-Q94/R/1G-R10 WIDS-515AD-G41-E15/R/1G-R10 WIDS-515AD-G41-Q94/R/1G-R10 WIDS-517A-G41-E15/R/1G-R10 WIDS-517A-G41-Q94/R/1G-R10 WIDS-517AD-G41-E15/R/1G-R10 WIDS-517AD-G41-Q94/R/1G-R10	Delete (Product Fail)
	2-177	Introduction	Ordering Information	WS-843GS / A130A / R-R20 WS-855GS / A130A / R-R20 WS-855GSATX / A130A / R-R20 WS-875GS / A130A / R-R20 WS-875GSATX / A130A / R-R20	WS-843GS / A130B / R-R20 WS-855GS / A130B / R-R20 WS-855GSATX / A130B / R-R20 WS-875GS / A130B / R-R20 WS-875GSATX / A130B / R-R20
	2-169	UPC-12A	Ordering Information	UPC-12A/GM45-CM575/WT-R/1GB-R20 UPC-12A/GM45-P8400/WT-R/2GB-R20 UPC-12A/GM45-T9400/WT-R/2GB-R20 UPC-12AH/GM45-CM575/WT-R/1GB-R11 UPC-12AH/GM45-P8400/WT-R/2GB-R11 UPC-12AH/GM45-T9400/WT-R/2GB-R11	UPC-12A/GM45-CM5R/1G-R20 UPC-12A/GM45-P84R/2G-R20 UPC-12A/GM45-T94R/2G-R20 UPC-12AH/GM45-CM5R/1G-R11 UPC-12AH/GM45-P84R/2G-R11 UPC-12AH/GM45-T94R/2G-R11
2-205	Introduction	Packing List	Length: 1800 mm Length: 1500 mm (For AFL-07M~12M and AFL-15M~W19M USB model)	RS-232 cable is for R models USB cable is for USB models	
4. RISC-based Solution	4-8	IOVU-570M	Introduction (on product picture)	Preinstalled Windows® CE5.0 or ARM-Linux boot from secure digital card	Preinstalled Windows® CE5.0 boot from secure digital card