

IEI Technology Corp.
2012 Catalog Correction (Panel Catalog)

Correction period: 2012.6.1~2012.6.30

Category	Page	Model Name	Location	Original Data	Correction
2. Automation Panel Solutions	2-24	AFL2-W15A	Optional Kit	AFL2-W15A-N270/PC: OS Win 7: AFL2CF-W15-N270-WES7E-R10 / AFL2CF-W15-N270-WES7P-R10 (2 GB CF card)	AFL2-W15A: OS Win 7: AFL2CF-W15-N270-WES7E-R10 / AFL2CF-W15-N270-WES7P-R10 (4 GB CF card)
				AFL2-W15A-780E/PC: OS Win 7: AFL2CF-W15-780-WES7E-R10 / AFL2CF-W15-780-WES7P-R10 (2 GB CF card)	AFL2-W15A-780E/PC: OS Win 7: AFL2CF-W15-780-WES7E-R10 / AFL2CF-W15-780-WES7P-R10 (4 GB CF card)
			Ordering Information	AFL2-W15A-N270/PC/1G-R11: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, Projected capacitive touchscreen, 1.3 M camera, microphone, 1GB DDR2 RAM, RoHS	AFL2-W15A-N270/PC/1G-R12: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, Projected capacitive touchscreen, 1.3 M camera, microphone, 1GB DDR2 RAM, without expansion, R12
				AFL2-W15A-N270/PC-EM/1G-R11: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, Projected capacitive touchscreen, 1.3 M camera, microphone, 1GB DDR2 RAM, EM card reader	AFL2-W15A-N270/PC-EM/1G-R12: 15.6" 250cd/m ² WXGA+ fanless panel PC with Intel® Atom™ N270 1.6 GHz, 802.11b/g/n wireless module, Projected capacitive touchscreen, 1.3 M camera, microphone, 1GB DDR2 RAM, EM card reader, without expansion, R12
	2-178	UPC-V312-D525	Specifications	SSD: CF Type II socket / mSATA (optional)	SSD: CF Type II socket
				Expansion Slot: Mini PCIe slot for mSATA (Optional)	Deleted
	2-188			SSD: CF Type II socket / mSATA (optional)	SSD: CF Type II socket
				Expansion Slot: Mini PCIe slot for mSATA (Optional)	Deleted