

IEI Integration Corp.
2014/2015 Catalog Correction (IPC/PPC Catalog)

Correction period: 2015.2.1~2015.2.28

| Catalog | Page | Model Name | Correction |
|---------|---------------|---|---|
| IPC | 1-138 | WAFER-PV-N4552/D5252 | Model name WAFER-PV-N4552/D5252 changed to WAFER-PV-D5252/D4252/N4552 CPU: Intel® Atom™ D525 dual-core processor 1.8GHz/1MB L2 cache Intel® Atom™ D425 single-core processor 1.8GHz/512KB L2 cache Intel® Atom™ N455 single-core processor 1.66GHz/512KB L2 cache Order Information: Add Part no.: WAFER-PV-D4252-R11 3.5" SBC with Intel® Atom™ D425 1.8GHz, DDR3, VGA/LVDS, dual GbE, USB 2.0 and SATA 3Gb/s, audio, RoHS |
| | 1-145 | PM-LX2 | Ordering Information: Remove FDD Cable |
| | 1-41 | HPE-3S1-R40 HPE-3S2-R40 HPE-4S1-R40 | Model Name all changed to: HPE-3S1- R41 HPE-3S2- R41 HPE-4S1- R41 |
| | 1-42 | HPE-5S1-R50 HPE-6S1-R40 | Model Name all changed to: HPE-5S1- R51 HPE-6S1- R41 |
| | 1-43 | HPE-8S0-R40 | Model Name changed to: HPE-8S0- R41 |
| | 1-88 | eKINO-BT | Power Supply: 9V~ 26V |
| PPC | 1-27 | ICEFIRE2-T10-HU-R10 ICEFIRE2-T10-TR-R10 ICEFIRE2-T10-ET-R10 | Model Name all changed to: ICEFIRE2-T10-HU- R11 ICEFIRE2-T10-TR- R11 ICEFIRE2-T10-ET- R11 |
| | 1-28 | ICEFIRE 2 | Packing List: Delete Stylus Optional Accessory List: Delete ICEFIRE-T10A-DSNM-R10 & Stylus |
| | 2-135 | UPC-V315-NM70 | Power note: power adapter supports operating temperature 0 to + 40 deg. C |
| | | UPC-V315-QM77 | |
| | 2-137 | UPC-V312-D525 | |
| | 2-140 | DM-F15A | Cutout Dimensions: 284.6 x 360.1 (mm) |
| | 1-69 | IOVU-430S | 1. IOVU-430S-CE6/ST/-R11 2. microSD card slot |
| | 2-140 | DM-F17A | Cutout dimenssion: 323 X 390 |
| 2-132 | UPC-V315-QM77 | Viewing Angle(V/H): 160° / 140° | |