

IEI Integration Corp.
2016 Catalog Correction

Correction period: 2016.08.01~2016.8.31

Catalog	Page	Model Name	Correction
IPC Product Catalog	1-25	WSB-H810	Ordering Information: 32200-015100-RS change to 19800-000049-RS Description: LPT flat cable, 240mm, P=2.54
	1-114	NANO-BTW2/BT-i1	Product photo and Dimensions Drawing revised
	1-49	IPX-9S-RS-R41	Product photo revised
	1-165	MPCIE-DLAN-R10	Ethernet Controller: Dual Intel(R) I210-IT
	1-26	WSB-H610	WSB-H610 change to R11 version
	1-87	tKINO-BW	Power Consumption 12V@1.61A (Intel® Celeron® N3710 CPU with two 4 GB 1600 MHz DDR3L memory)
			Ordering Information tKINO-BW-N4-R10: Thin Mini-ITX SBC supports Intel® Pentium® quad-core processor N3710 up to 2.56GHz (6W), VGA/LVDS/DP+HDMI, SATA, dual GbE, USB 3.0, HD Audio and RoHS
			Ordering Information tKINO-BW-N3-R10: Thin Mini-ITX SBC supports Intel® Celeron® quad-core processor N3160 up to 2.24GHz (6W), VGA/LVDS/DP+HDMI, SATA, dual GbE, USB 3.0, HD Audio and RoHS
			Ordering Information tKINO-BW-N2-R10: Thin Mini-ITX SBC supports Intel® Celeron® dual-core processor N3060 up to 2.48GHz (6W), VGA/LVDS/DP+HDMI, SATA, dual GbE, USB 3.0, HD Audio and RoHS
			Ordering Information tKINO-BW-N1-R10**: Thin Mini-ITX SBC supports Intel® Celeron® dual-core processor N3010 up to 2.24GHz (4W), VGA/LVDS/DP+HDMI, SATA, dual GbE, USB 3.0, HD Audio and RoHS
			Ordering Information 32205-002700-100-RS: RS-232/422/485 cable, 200mm, P=2.0
			Delete: 32205-003800-100-RS-RS-422/485 cable, 200mm, P=2.0
	1-60	IMBA-H110	Mutiple => Multiple
	3-17	EBC-2200	Specification > Reliability> Mounting Wallmount, VESA 75
1-127	WAFER-BW	Expansion 2 x Full/Half-size PCIe Mini card slot (1 w/ SIM holder) (1 w/ mSATA support: share SATA signal from SATA2)	
1-149	TPM-IN02	Add TPM-IN02 Sku	
2-57	AFL-08AH-LX	Audio delete	
	AFL-07A-LX		
	2-58	AFL-08AH-LX	Ordering Information AFL-08AH-LX/R/512-R24 8.4" 450 cd/m ² , SVGA fanless panel PC with AMD LX-800 CPU, AT/ATX mode, 802.11b/g Wireless Module, Touch screen and 512MB DDR RAM, R24
2-82		Power Adapter: P/N: 63040-010036-121-RS 36W Power Adapter Input: 90 - 264V AC, 50/60Hz Output: 12V DC	

Solution Catalog

2-83	PPC-F series	Power Adapter: P/N: 63040-010060-110-RS 60W Power Adapter Input: 90 - 264V AC, 50/60Hz Input: 90 - 264V AC, 50/60Hz Output: 12V DC
2-83		Power Adapter: P/N: 63040-010036-121-RS
2-86		Power Adapter: P/N: 63040-010060-110-RS
2-76	PPC-F06-BT	Input Interface I/O ports: 2 x RJ45 LAN port
2-152	DM-F19A	LCD Display 19(5:4)
3-2	POC-W22A	Rear 1 x DC Jack 1 x 1.5KV isolation COM Port 1 x GbE LAN port 2 x USB 3.0 port
3-12		Bottom 1 x RJ11 for barcode scanner (1D/2D) 1 x GbE LAN port 2 x USB 3.0 port 1 x HDMI Output
3-13		Other 2 x USB 2.0 port (Side) 1 x Audio out (Side) 1 x Mic in (Side) 2 x Speakers (Side: Both left and right) 1 x Digital Mic (Front, Bottom) 1 x 6-Key OSD (Front)
4-58	DRPC-120-BT	RS-232: 2 x DB-9 w/3KV isolation protection*
		RS-422/485: 2 x DB-9 w/3KV isolation protection*
	DRPC-100-CV	RS-422/485: 2 x DB-9 w/3KV isolation protection*
		RS-232: 2 x DB-9 w/3KV isolation protection*
Specifications	Add: * COM Port isolated 3kv for 1 sec, 2.5kv for 1 minute	
2-153	DM-F19A	DVI cable: 32200-086600-RS
		HDMI cable: N/A
2-100	PPC-5150A-H61	Dimension: Cut out size revised to 387 x 286
2-76	PPC-F08B-BT	I/O Ports and Switches delete: 2 x USB 2.0
2-82		
2-82	PPC-F08B-BT	RAM: 1 x 204-pin DDR3L SO-DIMM slots (max. 8GB)
	PPC-F10B	
3-13	POC-W22A	I/O Power input revise to 12~28V
2-9	AFL3-08A-BT	I/O Ports & Switch: 2 x USB 2.0

IEI Integration Corp.
2016 Catalog Correction

	4-61	UIBX-250	RS-422/485 => COM Port
--	------	----------	------------------------