

Correction period: 2011.6.1~2011.6.30

Category	Page	Model Name	Location	Original Data	Correction
1. Industrial Computing Solutions	1-90	KINO-945GSE2	Specifications	Temperature Operation: KINO-945GSE2-N270-R10: 0°C ~ 60°C KINO-945GSE2-N270W-R10: -20°C ~ 70°C	Deleted
			Ordering Information	KINO-945GSE2-N270W-R10 Mini-ITX SBC with Intel® Atom™ N270 1.6G, 12V DC input, VGA/ 18+24 bits LVDS/HDTV, PCIe GbE, USB2.0, SATA and Audio, -20~70°C	Deleted
	1-116	WAFER-PVD4251/N4551/D5251	Specifications	Power Consumption 1.7A @ 12V(Intel® Atom™ D525 with 2GB 1066MHz DDR3) 1.52A @ 12V(Intel® Atom™ D425 with 2GB 1066MHz DDR3) 1.33A @ 12V(Intel® Atom™ N455 with 2GB 1066MHz DDR3)	Power Consumption 1.7A @ 12V(Intel® Atom™ D525 with 1GB 1066MHz DDR3) 1.52A @ 12V(Intel® Atom™ D425 with 1GB 1066MHz DDR3) 1.33A @ 12V(Intel® Atom™ N455 with 1GB 1066MHz DDR3)
3. Embedded System	3-26	EBC-2100/2101	System Function	EBC-2100 LPT: N/A Audio: *4 x Audio jack	EBC-2100 LPT: *1 Audio: *3 x Audio jack
				EBC-2101 LPT: *1	EBC-2101 LPT: N/A
7. Power Supply/Peripherals	7-26	ACE-A140A	Dimensions		Changed