

Correction period: 2013.10.1~2013.10.31

Category	Page	Model Name	Location	Original Data	Correction
1. IEI Mobile Solution	1-26	ICEROCK3	Features	Intel® Atom™ N2800 1.6GHz processor	Intel® Atom™ N2600 1.6GHz processor
	1-28	ICEROCK3	Specifications	CPU: Intel® Atom™ N2800 1.6GHz Storage 8GB mSATA	CPU: Intel® Atom™ N2600 1.6GHz Storage: 32GB MLC mSATA
			Ordering Information		Changed as follow: ICEROCK3-T10-ET-R10: Intel Atom N2600 CPU, Capacitive touch, IPS panel, 2GB RAM, 32G SSD, 802.11 b/g/n&BT, RFID, 1.3M camera,RFID, WS7P, RoHs
					ICEROCK3-T10-HU-R10: Intel Celeron 827E CPU, Capacitive touch, IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, RFID, 1.3M camera, GPS, Barcode Reader, RFID, 2nd battery, WS7P, RoHs
					ICEROCK3-T10-ETC-R10: Intel Celeron 827E CPU, Capacitive touch, IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, RFID, 1.3M camera, 2nd battery, WS7P, RoHs
					ICEROCK3-T10-HUI-R10: Intel I7-3517 CPU, Capacitive touch, IPS panel, 8GB RAM, 32G SSD, 802.11 b/g/n&BT, 3.75G, RFID, 1.3M/5M camera, 2nd battery, GPS, barcode, WS7P, RoHs
	Model Variations		Please see attached link for detail changed. http://www.ieiworld.com/ieimobile/ICEROCK3/Datasheet/ICEROCK3-Datasheet.pdf		
	1-35	ICECARE-10W	Features	10.1" TFT LCD with resistive touch Intel® Atom™ N2800 1.86GHz processor	10.1" TFT LCD with capacitive touch Intel® Atom™ N2600 1.6GHz processor
			Applications	Powered by the Intel® Atom™ N2600 processor and Windows® Embedded Standard 7 operating system	Powered by the Intel® Atom™ N2800 processor and Windows® Embedded Standard 7 operating system
	1-37	ICECARE-10W	Specifications	Touch Screen: Resistive type CPU: Intel® Atom™ N2800 1.6GHz Memory On-board 32GB DDR3	Touch Screen: Capacitive type CPU: Intel® Atom™ N2600 1.6GHz Memory: On-board 2GB DDR3
	1-37	ICECARE-10W	Ordering Information		Changed as follow: ICECARE-10W-R10: Intel® Atom™ N2600 1.6GHz CPU, Capacitive touch, Non-IPS panel, 2GB RAM, 32G SSD, 802.11 b/g/n&BT, 1D/2D Barcode, MSR, SCR, RFID, WS7P, RoHs
					ICECARE-10W-ET-R10 Intel® Atom™ N2600 1.6GHz CPU, Capacitive touch, Non-IPS panel, 2GB RAM, 32G SSD, 802.11 b/g/n&BT, RFID, WS7P, RoHs
					ICECARE-10W-CE-R10: Intel® Celeron 827E 1.4GHz CPU, Capacitive touch, Non-IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, 1D/2D Barcode, MSR, SCR, RFID, WS7P, RoHs
					ICECARE-10W-CE-ET-R10: Intel® Celeron 827E 1.4GHz CPU, Capacitive touch, Non-IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, RFID, WS7P, RoHs
					ICECARE-10W-I7-R10: Intel® Core I7-3517U 1.9GHz CPU, Capacitive touch, IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, 1D/2D Barcode, MSR, SCR, RFID, WS7P, RoHs
					ICECARE-10W-I7-ET-R10: Intel® Core I7-3517U 1.9GHz CPU, Capacitive touch, IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, RFID, WS7P, RoHs
	1-37	ICECARE-10W	Model Variations		Changed as follow: Intel Atom N2600 1.6GHz CPU, Capacitive touch, Non-IPS panel, 2GB RAM, 32G SSD, 802.11 b/g/n&BT, 1D/2D Barcode, MSR, SCR, RFID, WS7P, RoHs
					Intel Atom N2600 1.6GHz CPU, Capacitive touch, Non-IPS panel, 2GB RAM, 32G SSD, 802.11 b/g/n&BT, RFID, WS7P, RoHs

					Intel Celeron 827E 1.4GHz CPU, Capacitive touch, Non-IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, 1D/2D Barcode, MSR, SCR, RFID, WS7P, RoHs
					Intel Celeron 827E 1.4GHz CPU, Capacitive touch, Non-IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, RFID, WS7P, RoHs
					Intel Core I7-3517U 1.9GHz CPU, Capacitive touch, IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, 1D/2D Barcode, MSR, SCR, RFID, WS7P, RoHs
					Intel Core I7-3517U 1.9GHz CPU, Capacitive touch, IPS panel, 4GB RAM, 32G SSD, 802.11 b/g/n&BT, RFID, WS7P, RoHs
2. Automation Panel Solutions	2-59	AFL-10A	Specification	Power Adapter: P/N: 63000-FSP036RAB608-RS 36W Power Adapter Input: 90VAC~264VAC, 50/60Hz Output: 12VDC	Power Adapter: P/N: 63040-010060-030-RS 60W Power Adapter Input: 90VAC~264VAC, 50/60Hz Output: 12VDC
	2-61		Packing List	Power Adpater: 63000-FSP036RAB608-RS 63040-010060-040-RS (for AFL-10A-N26)	Power Adpater: 63000-FSP036RAB608-RS 63040-010060-040-RS (for AFL-10A-N270 and AFL-10A-N26)
	2-62	AFL-12A	Specification	Power Adapter: P/N: 63000-FSP050DABA1405-RS 36W Power Adapter Input: 90VAC~264VAC, 50/60Hz Output: 12VDC	Power Adapter: P/N: 63040-010060-030-RS 60W Power Adapter Input: 90VAC~264VAC, 50/60Hz Output: 12VDC
	2-64		Packing List	90~264V AC; 12V DC; 36W (for LX) 90~264V AC; 12V DC; 50W (for LXPOS,N270) 90~264V AC; 12V DC; 60W (for N2600)	90~264V AC; 12V DC; 36W (for LX) 90~264V AC; 12V DC; 60W (for N270 and N2600)