

Correction period: 2013.2.1~2013.2.28

Category	Page	Model Name	Location	Original Data	Correction
2. Automation Panel Solutions	2-25	AFL2-17A-H61	Ordering Information	AFL2-17A-H61-i5/R-R11: 17" 350cd/m ² SXGA panel PC, Core i5 Dual Core 2xxxT CPU (Above 2.7GHz), TDP 35W, 2GB DDR3 RAM*2, 802.11b/g/n wireless module, resistive touch screen, 2M camera, microphone, R11	AFL2-17A-H61-i5/R-R12: 17" 350cd/m ² SXGA panel PC, Core i5 Dual Core 2xxxT CPU (Above 2.7GHz), TDP 35W, 2GB DDR3 RAM*2, 802.11b/g/n wireless module, resistive touch screen, 2M camera, microphone, R12
				AFL2-17AB-H61-i5/R-R11: 17" 350cd/m ² SXGA panel PC, Core i5 Dual Core 2xxxT CPU (Above 2.7GHz), TDP 35W, 2GB DDR3 RAM*2, 802.11b/g/n wireless module, resistive touch screen, 2M camera, microphone, without LED bar, R11	AFL2-17AB-H61-i5/R-R12: 17" 350cd/m ² SXGA panel PC, Core i5 Dual Core 2xxxT CPU (Above 2.7GHz), TDP 35W, 2GB DDR3 RAM*2, 802.11b/g/n wireless module, resistive touch screen, 2M camera, microphone, without LED bar, R12
				AFL2-17A-H61-i5/PC-R11: 17" 350cd/m ² SXGA panel PC, Core i5 Dual Core 2xxxT CPU (Above 2.7GHz), TDP 35W, 2GB DDR3 RAM*2, 802.11b/g/n wireless module, projected capacitive touchscreen, 2M camera, microphone, R11	AFL2-17A-H61-i5/PC-R12: 17" 350cd/m ² SXGA panel PC, Core i5 Dual Core 2xxxT CPU (Above 2.7GHz), TDP 35W, 2GB DDR3 RAM*2, 802.11b/g/n wireless module, projected capacitive touchscreen, 2M camera, microphone, R12
	2-148	PPC-3708A-N26 PPC-3708A-N270 PPC-3708GS-945 PPC-3710A-N26 PPC-3710A-N270 PPC-3710GS-945	PPC Series 8.4"~10.4" PPC Selection Guide	RAM: One 200-pin SO-DIMM socket, supporting DDRIII 800MHz modules for up to 2GB	RAM: One 204-pin SO-DIMM socket, supporting DDRIII 800MHz modules for up to 2GB
				PPC-3712A-N26 PPC-3712A-N270 PPC-3712GXS-945	PPC Series 12.1" PPC Selection Guide
	2-152	PPC-3708A-N270 PPC-3708A-N26 PPC-3708GS-945	Features	3. One internal 2.5" SATA HDD and CF slot	Deleted
			Specifications	RAM: One 200-pin SO-DIMM socket, supporting DDRIII 800MHz modules for up to 2GB	RAM: One 204-pin SO-DIMM socket, supporting DDRIII 800MHz modules for up to 2GB
	2-155	PPC-3710A-N270 PPC-3710A-N26 PPC-3710GS-945	Features	3. One internal 2.5" SATA HDD and CF slot	Deleted
			Specifications	RAM: One 200-pin SO-DIMM socket, supporting DDRIII 800MHz modules for up to 2GB	RAM: One 204-pin SO-DIMM socket, supporting DDRIII 800MHz modules for up to 2GB
	2-156		Packing List	Power Adapter: 63000-FSP084DMBA1308-RS: 84W, 90VAC~264VAC for PPC-3710GS-945 Socket Type	Power Adapter: 63000-FSP084DMBA1308-RS: 84W, 90VAC~264VAC for PPC-3710GS-945
	2-158	PPC-3712A-N270 PPC-3712A-N26 PPC-3712GXS-945	Features	5. One internal 2.5" SATA HDD and CF slot	Deleted
	2-165	PPC-5152-D525	Options	Rack Mounting Kit: RK-150MS2-R10	Deleted
	2-166	PPC-5150A-H61 PPC-5150A/9455 PPC-5150A-G41	Features	* Optional PCIe Mini 802.11b/g/n wireless module	Deleted
	2-167		IQ Mounting Options	Rack Mount Kit: RK-150MS-R10 (for PPC-5150A series)	Rack Mount Kit: RK-150MS-R10
2-169	PPC-5170A-H61 PPC-5170A/9455 PPC-5170A-G41	Features	* Optional PCIe Mini 802.11b/g/n wireless module	Deleted	
		IQ Mounting Options	Rack Mount Kit: RK-170MS-R10 (for PPC-5170A series)	Rack Mount Kit: RK-170MS-R10	
2-172	PPC-5190A-H61 PPC-5190A/9455 PPC-5150A-G41	Features	* Optional PCIe Mini 802.11b/g/n wireless module	Deleted	
2-175	WIDS-515A-H61 WIDS-517A-H61	WIDS Series Selection Guide	SSD: CF Type II, mSATA (optional)	SSD: CF Type II, mSATA	
	S12A(SR)-N270	Industrial Vertical Market PPC Selection Guide	Brightness (cd/m ²): 400 (1000) Contrast Ratio: 500 : 1 (700 : 1) Viewing Angle (V/H): 120°/100° (120°/130°) Backlight MTBF (hrs): 60000 (50000)	Brightness (cd/m ²): 400 (1300) Contrast Ratio: 500 : 1 (700 : 1) Viewing Angle (V/H): 120°/100° (160°/140°) Backlight MTBF (hrs): 60000 (100000)	

2-183	S12ASR-N270	Specifications	Brightness (cd/m ²): 1000 LCD Color: 262K Viewing Angle (V/H): 120°/130° Backlight MTBF (hrs): 50000	Brightness (cd/m ²): 1300 LCD Color: 16.7M Viewing Angle (V/H): 160°/140° Backlight MTBF (hrs): 100000
2-184	S12ASR	Ordering Information	S12ASR/R/1/1-C6-R21: 12.1" 1000 cd/m ² IP67 panel PC with Intel® Atom™ N270, CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 1GB compact flash with Windows CE 6.0 operating system, R21	S12ASR/R/1/1-C6-R30: 12.1" 1300 cd/m ² IP67 panel PC with Intel® Atom™ N270, CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 1GB compact flash with Windows CE 6.0 operating system, R30
			S12ASR/R/1/4-X-R21: 12.1" 1000 cd/m ² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 4GB compact flash with Windows XP Embedded operating system, R21	S12ASR/R/1/4-X-R30: 12.1" 1300 cd/m ² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 4GB compact flash with Windows XP Embedded operating system, R30
			S12ASR/R/1/16-X-R21: 12.1" 1000 cd/m ² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 160GB SATA HDD with Windows XP Embedded operating system, R21	S12ASR/R/1/16-X-R30: 12.1" 1300 cd/m ² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 160GB SATA HDD with Windows XP Embedded operating system, R30
			S12ASR/R/1/4-L-R21: 12.1" 1000 cd/m ² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 4GB compact flash with LINUX operating system, R21	S12ASR/R/1/4-L-R30: 12.1" 1300 cd/m ² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 4GB compact flash with LINUX operating system, R30
			S12ASR/R/1/16-L-R21: 12.1" 1000 cd/m ² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 160GB SATA HDD with LINUX operating system,R21	S12ASR/R/1/16-L-R30: 12.1" 1300 cd/m ² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module,touch screen,1GB DDR2 553 MHz, M12 connectors and 160GB SATA HDD with LINUX operating system,R30
2-187	UPC-V315-QM77	Power Requirement	9~36V DC	Power1:9V~36V(+/-0.3V) Power2:10.5V~36V(+/-0.3V)
	UPC-V315-NM70	Power Requirement	9~36V DC	Power1:9V~36V(+/-0.3V) Power2:10.5V~36V(+/-0.3V)
2-188	UPC-V315	Ordering Information	UPC-V315 ordering Information changed as right column.	UPC-V315-QM77-i7/R/2G-R10: 15" 400cd/m ² XGA fanless full IP65 panel PC with Mobile Intel® QM77 Express Chipset and Intel® Core™ i7-3517UE Processor, 802.11a/b/g/n wireless module, resistive touch screen, 2M camera,microphone,2GB DDR3 RAM, R10
				UPC-V315-QM77-i3/R/2G-R10: 15" 400cd/m ² XGA fanless full IP65 panel PC with Mobile Intel® QM77 Express Chipset and Intel® Core™ i3-3217UE Processor, 802.11a/b/g/n wireless module, resistive touch screen, 2M camera,microphone,2GB DDR3 RAM, R10
				UPC-V315-NM70-C/R/2G-R10: 15" 400cd/m ² XGA fanless full IP65 panel PC with Mobile Intel® NM70 Express Chipset and Intel® Celeron® Processor 847, 802.11a/b/g/n wireless module, resistive touch screen, 2M camera,microphone,2GB DDR3 RAM, R10
2-190	UPC-V315	Options	OS changed as right column.	EM RFID Kit: UPC-EM-RFID-KIT01-R10 Mifare RFID Kit: UPC-MF-RFID-KIT01-R10 OS: Win XPE (CD-ROM): UPC-V315-XPE-R10 OS: Linux (CD-ROM): UPC-V315-LNX-R10 OS: Win 7 Embedded (DVD-ROM): UPC-V315-W7E-R10
2-213	DM-150GS	Specifications	Brightness (cd/m ²): 350 Contrast Ratio: 500 : 1 Viewing Angle (H/V) : 120° / 100°	Brightness (cd/m ²): 400 Contrast Ratio: 700 : 1 Viewing Angle (H/V) : 120° / 140°
	DM-170GS	Specifications	Brightness (cd/m ²): 300	Brightness (cd/m ²): 350
	DM-190GS	Specifications	Brightness (cd/m ²): 450	Brightness (cd/m ²): 350

2-214	DM-150G	Ordering Information	DM-150GS/R-R20: 15" 350cd/m ² XGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, R20, RoHS	DM-150GS/R-R30: 15" 400cd/m ² XGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, R30, RoHS
			DM-150GMS/R-R21: 15" 350cd/m ² XGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, 9~36V DC input, R21, RoHS	DM-150GMS/R-R30: 15" 400cd/m ² XGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, 9~36V DC input, R30, RoHS
	DM-170G	Ordering Information	DM-170GS/R-R20: 17" 300cd/m ² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, R20, RoHS	DM-170GS/R-R30: 17" 350cd/m ² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, R30, RoHS
			DM-170GMS/R-R21: 17" 300cd/m ² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, 9~36V DC input, R21, RoHS	DM-170GMS/R-R30: 17" 350cd/m ² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, 9~36V DC input, R30, RoHS
	DM-190G	Ordering Information	DM-190GS/R-R21: 19" 450cd/m ² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, R21, RoHS	DM-190GS/R-R30: 19" 350cd/m ² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, R30, RoHS
			DM-190GMS/R-R22: 19" 450cd/m ² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, 9~36V DC input, R22, RoHS	DM-190GMS/R-R30: 19" 350cd/m ² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, 9~36V DC input, R30, RoHS
2-217	SRM-121XA SRM-KIT121XA	Specifications	Brightness (cd/m ²): 1000 Display Color: 262k	Brightness (cd/m ²): 1300 Display Color: 16.7M
2-218	12.1" XGA SRM Series	Ordering Information	SRM-121XA/R-R30: 12.1" 1000cd/m ² sun readable XGA LCD monitor, Aluminum Front Panel, Silver Color, w/VGA and DVI-D input, w/12.1" RS-232 and USB Touch Screen, R30, RoHS	SRM-121XA/R-R40: 12.1" 1300cd/m ² sun readable XGA LCD monitor, Aluminum Front Panel, Silver Color, w/VGA and DVI-D input, w/12.1" RS-232 and USB Touch Screen, R40, RoHS
			SRM-121XMA/R-R30: 12.1" 1000cd/m ² sun readable XGA LCD monitor, Aluminum Front Panel, Silver Color, w/VGA and DVI-D input, w/9~36V DC input, w/12.1" RS-232 and USB Touch Screen, R30, RoHS	SRM-121XMA/R-R40: 12.1" 1300cd/m ² sun readable XGA LCD monitor, Aluminum Front Panel, Silver Color, w/VGA and DVI-D input, w/9~36V DC input, w/12.1" RS-232 and USB Touch Screen, R40, RoHS
2-221	LCD-KIT150G	Specifications	Brightness (cd/m ²): 350 Contrast Ratio: 500 : 1 Viewing Angle(H/V): 120/100	Brightness (cd/m ²): 400 Contrast Ratio: 700 : 1 Viewing Angle(H/V): 160/140
	LCD-KIT170G	Specifications	Brightness (cd/m ²): 300 Viewing Angle (H/V) : 160/160	Brightness (cd/m ²): 350 Viewing Angle (H/V) : 170/160
	LCD-KIT150G	Ordering Information	LCD-KIT150G-R20: 15" 350cd/m ² XGA TFT LCD kit, VGA and DVI-D input, R20, RoHS	LCD-KIT150G-R30: 15" 400cd/m ² XGA TFT LCD kit, VGA and DVI-D input, R30, RoHS
			LCD-KIT150GM-R21: 15" 350cd/m ² XGA TFT LCD kit, VGA and DVI-D input, 9~36V DC input, R21, RoHS	LCD-KIT150GM-R30: 15" 400cd/m ² XGA TFT LCD kit, VGA and DVI-D input, 9~36V DC input, R30, RoHS
	LCD-KIT170G	Ordering Information	LCD-KIT170GS-R20: 17" 300cd/m ² SXGA TFT LCD kit, VGA and DVI-D input, R20, RoHS	LCD-KIT170GS-R30: 17" 350cd/m ² SXGA TFT LCD kit, VGA and DVI-D input, R30, RoHS
			LCD-KIT170GM-R21: 17" 300cd/m ² SXGA TFT LCD kit, VGA and DVI-D input, 9~36V DC input, R21, RoHS	LCD-KIT170GM-R30: 17" 350cd/m ² SXGA TFT LCD kit, VGA and DVI-D input, 9~36V DC input, R30, RoHS
2-228	AFL-15M			EOL
	AFL-17M	Specifications	Brightness (cd/m ²): 380 Contrast Ratio: 1000:1	Brightness (cd/m ²): 350 Contrast Ratio: 700:1
	AFL-19M		Brightness (cd/m ²): 450	Brightness (cd/m ²): 350
2-231	AFL-15M	Ordering Information	AFL-15M/R-R20 AFL-15M-USB/R-R20	EOL
	AFL-17M	Ordering Information	AFL-17M/R-R20: 17" 380cd/m ² SXGA LCD monitor, plastic front panel, gray color, With 17" RS-232 touch screen R20, RoHS	AFL-17M/R-R20: 17" 350cd/m ² SXGA LCD monitor, plastic front panel, gray color, With 17" RS-232 touch screen R20, RoHS

			AFL-17M-USB/R-R20: 17" 380cd/m ² SXGA LCD monitor, plastic front panel, gray color, With 17" USB touch screen R20, RoHS	AFL-17M-USB/R-R20: 17" 350cd/m ² SXGA LCD monitor, plastic front panel, gray color, With 17" USB touch screen R20, RoHS
	AFL-19M	Ordering Information	AFL-19M/R-R20: 19" 450cd/m ² SXGA LCD monitor, plastic front panel, gray color, With 19" RS-232 touch screen R20, RoHS	AFL-19M/R-R20: 19" 350cd/m ² SXGA LCD monitor, plastic front panel, gray color, With 19" RS-232 touch screen R20, RoHS
			AFL-19M-USB/R-R20: 19" 450cd/m ² SXGA LCD monitor, plastic front panel, gray color, With 19" USB touch screen R20, RoHS	AFL-19M-USB/R-R20: 19" 350cd/m ² SXGA LCD monitor, plastic front panel, gray color, With 19" USB touch screen R20, RoHS
2-231	SRM-KIT	Ordering Information	SRM-KIT121XA-R20: 12.1" 1000 cd/m ² Sun Readable XGA TFT LCD kit, VGA and DVI-D input, R20, RoHS	SRM-KIT121XA-R30: 12.1" 1000 cd/m ² Sun Readable XGA TFT LCD kit, VGA and DVI-D input, R30, RoHS
			SRM-KIT121XMA-R21: 12.1" 1000 cd/m ² Sun Readable XGA TFT LCD kit, VGA and DVI-D input, w/9-36V DC input, R21, RoHS	SRM-KIT121XMA-R30: 12.1" 1000 cd/m ² Sun Readable XGA TFT LCD kit, VGA and DVI-D input, w/9-36V DC input, R30, RoHS
			SRM-KIT150G-R20: 15" 800 cd/m ² Sun Rdadable XGA TFT LCD kit, VGA and DVI-D input, R20, RoHS	SRM-KIT150G-R30: 15" 800 cd/m ² Sun Rdadable XGA TFT LCD kit, VGA and DVI-D input, R30, RoHS
			SRM-KIT150GM-R21: 15" 800 cd/m ² Sun Readable XGA TFT LCD kit, VGA and DVI-D input, w/9-36V DC input, R21, RoHS	SRM-KIT150GM-R30: 15" 800 cd/m ² Sun Readable XGA TFT LCD kit, VGA and DVI-D input, w/9-36V DC input, R30, RoHS