

Correction period: 2013.4.1~2013.4.30

Category	Page	Model Name	Location	Original Data	Correction
2. Automation Panel Solutions	2-37	AFL-15D(E)-N270	15" ~Wide 15.6" Selection Guide	Brightness (cd/m²): 350 or 250	Brightness (cd/m²): 250
				Viewing Angle (H/V): 140°/125° or 160°/160°	Viewing Angle (H/V): 160°/160°
				Backlight MTBF (hrs): 50000 or 40000	Backlight MTBF (hrs): 40000
	2-38	AFL-W15A-N270 AFL-W15A-GM45	15" ~Wide 15.6" Selection Guide	Backlight MTBF (hrs): 50000	Backlight MTBF (hrs): 50000 (LED backlighting)
		AFL-19i-HM55	17" ~19" Selection Guide	Viewing Angle (H/V) : 178°/178°	Viewing Angle (H/V) : 170°/160°
					Backlight MTBF (hrs) : 50000 (LED)
	2-63	AFL-15i(E)-HM55	Specifications	Brightness (cd/m²): 350 or 250	Brightness (cd/m²): 250
				Viewing Angle (H-V): 140°/125° or 160°/160°	Viewing Angle (H-V): 160°/160°
				Backlight MTBF: 50000 hrs or 40000 hrs	Backlight MTBF: 40000 hrs
				AFL-15A-N270/R/1G-R22: 15" 350cd/m² XGA fanless panel PC with Intel® Atom™ N270 1.6GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n wireless module, touch screen, R22	AFL-15A-N270/R/1G-R30: 15" 400cd/m² XGA fanless panel PC with Intel® Atom™ N270 1.6GHz CPU, 1GB DDR2 RAM, 802.11 b/g/n wireless module, touch screen, R30
				AFL-15i-HM55-P45/R/1G-R12: 15" 350cd/m² XGA panel PC with Intel® Celeron P4500 1.86G CPU, 1GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R12, RoHS	AFL-15i-HM55-P45/R/1G-R30: 15" 400cd/m² XGA panel PC with Intel® Celeron P4500 1.86G CPU, 1GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R30
				AFL-15i-HM55i3-35/R/2G-R12: 15" 350cd/m² XGA panel PC with Intel® Core™ i3-350M 2.26G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R12, RoHS	AFL-15i-HM55i3-35/R/2G-R30: 15" 400cd/m² XGA panel PC with Intel® Core™ i3-350M 2.26G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R30
	2-73	AFL-19i(E)-HM55	Specifications	AFL-15i-HM55i5-52/R/2G-R12: 15" 350cd/m² XGA panel PC with Intel® Core™ i5-520M 2.4G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R12, RoHS	AFL-15i-HM55i5-52/R/2G-R30: 15" 400cd/m² XGA panel PC with Intel® Core™ i5-520M 2.4G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R30
				AFL-15i-HM55i7-62/R/2G-R12: 15" 350cd/m² XGA panel PC with Intel® Core™ i7-620M 2.66G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R12, RoHS	AFL-15i-HM55i7-62/R/2G-R30: 15" 400cd/m² XGA panel PC with Intel® Core™ i7-620M 2.66G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R30
				Brightness (cd/m²): 450 Viewing Angle (H-V): 178° / 178° Backlight MTBF: 50000 hrs	Brightness (cd/m²): 350 Viewing Angle (H-V): 170° / 160° Backlight MTBF: 50000 hrs(LED backlighting)
				AFL-19i-HM55-P45/R/1G-R12: 19" 450cd/m² SXGA panel PC with Intel® Celeron® P4500 1.86G CPU, 1GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R12, RoHS	AFL-19i-HM55-P45/R/1G-R20: 19" 350cd/m² SXGA panel PC with Intel® Celeron® P4500 1.86G CPU, 1GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R20, RoHS
	2-146	S12A	Ordering Information	AFL-19i-HM55i3-35/R/2G-R12 : 19" 450cd/m² SXGA panel PC with Intel® Core™ i3-350M 2.26G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R12, RoHS	AFL-19i-HM55i3-35/R/2G-R20 : 19" 350cd/m² SXGA panel PC with Intel® Core™ i3-350M 2.26G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R20, RoHS
				AFL-19i-HM55i5-52/R/2G-R12: 19" 450cd/m² SXGA panel PC with Intel® Core™ i5-520M 2.4G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R12, RoHS	AFL-19i-HM55i5-52/R/2G-R20: 19" 350cd/m² SXGA panel PC with Intel® Core™ i5-520M 2.4G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R20, RoHS
				AFL-19i-HM55i7-62/R/2G-R12: 19" 450cd/m² SXGA panel PC with Intel® Core™ i7-620M 2.66G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R12, RoHS	AFL-19i-HM55i7-62/R/2G-R20: 19" 350cd/m² SXGA panel PC with Intel® Core™ i7-620M 2.66G CPU, 2GB DDR3 RAM, 802.11 b/g/n wireless module, touch screen, R20, RoHS
				Ordering information changed as right.	S12A/R/1/32-X-R30 12.1" 500 cd/m² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 320GB SATA HDD with Windows XP Embedded operating system, R30

				12.1" 500 cd/m² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 4GB compact flash with LINUX operating system, R30 S12A/R/1/32-L-R30 12.1" 500 cd/m² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 320GB SATA HDD with LINUX operating system, R30 12.1" 500 cd/m² IP67 panel PC with Intel® Atom™ N270, CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 1GB compact flash with Windows CE 6.0 operating system, R30 12.1" 500 cd/m² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 4GB compact flash with Windows XP Embedded operating system, R30 S12ASR/R/1/1-C6-R30 12.1" 1000 cd/m² IP67 panel PC with Intel® Atom™ N270, CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 1GB compact flash with Windows CE 6.0 operating system, R30 S12ASR/R/1/4-X-R30 12.1" 1000 cd/m² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 4GB compact flash with Windows XP Embedded operating system, R30 S12ASR/R/1/32-X-R30 12.1" 1000 cd/m² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 320GB SATA HDD with Windows XP Embedded operating system, R30 S12ASR/R/1/4-L-R30 12.1" 1000 cd/m² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 4GB compact flash with LINUX operating system, R30 S12ASR/R/1/32-L-R30 12.1" 1000 cd/m² IP67 panel PC with Intel® Atom™ N270 CPU 1.6GHz, 802.11 b/g/n wireless module, touch screen, 1GB DDR2 553 MHz, M12 connectors and 320GB SATA HDD with LINUX operating system, R30
2-211	Feature 4	Feature 4	New Feature 4	Feature 4
2-214	DM-190GMS/R-R22	Ordering Information	DM-190GMS/R-R22 19" 350cd/m² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, 9~36V DC input, R22, RoHS	DM-190GMS/R-R30 19" 350cd/m² SXGA LCD monitor, Aluminum front panel, Silver color, W/RS-232 and USB Touch screen, 9~36V DC input, R30, RoHS
2-217	SRM-121XA	Specifications	Brightness (cd/m²): 1300	Brightness (cd/m²): 1000
2-218	SRM-12	Ordering Information	SRM-121XA/R-R40: 12.1" 1300cd/m² sun readable XGA LCD monitor, Aluminum Front Panel, Silver Color, w/VGA and DVI-D input, w/12.1" RS-232 and USB Touch Screen, R40, RoHS	SRM-121XA/R-R30: 12.1" 1000cd/m² sun readable XGA LCD monitor, Aluminum Front Panel, Silver Color, w/VGA and DVI-D input, w/12.1" RS-232 and USB Touch Screen, R30, RoHS
			SRM-121XMA/R-R40: 12.1" 1300cd/m² sun readable XGA LCD monitor, Aluminum Front Panel, Silver Color, w/VGA and DVI-D input, w/9~36V DC input, w/12.1" RS-232 and USB Touch Screen, R40, RoHS	SRM-121XMA/R-R30: 12.1" 1000cd/m² sun readable XGA LCD monitor, Aluminum Front Panel, Silver Color, w/VGA and DVI-D input, w/9~36V DC input, w/12.1" RS-232 and USB Touch Screen, R30, RoHS

IEI Technology Corp.
2012 Catalog Correction (Panel Catalog)

5. Optional Peripherals	5-8	STAND-B19	Model name	STAND-B19	STAND-A21
			Ordering Information	STAND-B19-RS 15"~19" VESA 75x75mm/100x100mm PPC/Monitor Stand, support from 2.7KG to 7.3KG, Black, RoHS	STAND-A21 SE76, MODULE(OTHER),STAND- A21,STANDARD,00,HA741L,BLACK,222*432*2 52 MM,6~12KG,RoHS